



## Econova 5W-20 | Fully synthetic engine oil

### Property

- proven fuel saving and reduced emissions thanks to lowered HTHS viscosity
- keeps the engine clean and protects against wear and corrosion
- excellent cold starting characteristics
- Low SAPS technology with reduced content of sulphated ash, phosphorus and sulphur
- increases the service life of exhaust aftertreatment systems such as catalytic converters (SCR) and particulate filters (GPF/DPF) in gasoline and diesel engines

### Application area

- especially suitable for Ford
- only to be used in vehicles in which an engine oil viscosity of 5W-20 is recommended
- suitable for gasoline and diesel engines
- suitable for passenger cars and light commercial vehicles

### Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

### Typical properties

Property	Unit	Value
Viscosity SAE	-	5W-20
Color	-	brown
Viscosity @ 40°C	mm <sup>2</sup> /s	45
Viscosity @ 100°C	mm <sup>2</sup> /s	8.3
Viscosity index	-	162
Density @ 15°C	kg/l	0.855
Viscosity CCS @ -30°C	mPa.s	4100
Viscosity HTHS @ 150°C	mPa.s	2.6
Zinc content	ppm	880
Sulphated ash	g/100g	0.8
Pour Point	°C	-39
Flash Point	°C	220

### Available packaging

1 L bottle	Case 12 x 1 L bottles
50 kg drum (approx. 58 L)	175 kg drum (approx. 205 L)

### Specifications

ACEA C5
API SJ*, SL*, SL/CF*, SM*, SN/CF
Chrysler MS 6395
Fiat 9.55535-CR1
Ford M2C948-B
Jaguar Land Rover STJLR.03.5004

\* Additional Specifications