



Sensomatic | Fully synthetic automatic transmission fluid

Property

- outstanding seal compatibility
- very high resistance to wear, corrosion and foaming
- lower fuel consumption thanks to lower viscosity
- excellent low temperature behaviour
- smooth gear changing at all temperatures and under load

Application area

- not recommended for continuously variable transmissions (CVT)
- suitable for automatic transmissions where a Mitsubishi Dia-Queen ATF J3, ATF PA, Shell ATF M-1375.4 or a ZF Lifeguardfluid 6, Lifeguardfluid 8 or Lifeguardfluid 9 is recommended
- for todays 6 to 10-speed automatic transmissions of several manufacturers

Note

- Technical data subject to change without notice. Please observe the vehicle or machine manufacturer's directions. Please refer to the safety data sheet for further information.

Typical properties

Eigenschaft	Einheit	Wert
Color	-	red
Viscosity @ 40°C	cSt	26
Viscosity @ 100°C	cSt	5.7
Viscosity index	-	170
Density @ 15°C	kg/l	0.845
Viscosity Brookfield @ -40°C	mPa.s	10000
Pour Point	°C	-46
Flash Point	°C	180

Available packaging

1 L bottle	Case 12 x 1 L bottles
50 kg drum (approx. 59 L)	175 kg drum (approx. 207 L)

Specifications

Aisin Warner AW-1, AW-2
Fiat 9.55550-AV2, AV3, AV5, AV6
Ford Mercon LV (M2C938-A), Mercon SP, Mercon ULV (M2C949-A)
GM DEXRON HP, ULV, VI
Honda ATF DW-1, Type 3.0, Type 3.1, Z-1
JASO 1A, 1A-LV
Mazda ATF-A7, ATF-FZ
MB 236.12, 236.14, 236.15, 236.16*, 236.17, 236.41
MM MA1, SP-IV, SP-IV M, SP-IV RR
Nissan Matic G, Matic J, Matic P, Matic S, Matic W
Toyota WS (JWS 3324/NWS 9638)
VW G 052 533, G 055 005, G 055 162, G 055 540, G 060 162

* Additional Specifications